

Tender Number **XXXXXXXXXX** / Project name: **XXXXXXX**
Date: **XX. XX. XXXX**

Item.	Qty.	Technical description	Price per unit	Amount
		Task The solids (mud flakes, mud, fibers, Sands, etc.) in the treated wastewater must be kept in suspension and the velocity of the liquid in the complete basin shall have a velocity between 0,20 - 0,30 m/s to avoid the sedimentation of solids. Technical details of the basins Activated sludge: 2 - 6 g/l dry solids Sludge Volume Index (SVI) 50 - 150 ml/g Number of basins: X Basin shape: XXXXXXXXXXXXXXXXXX Dimensions: diameter X m / length X m / channel width X m Water depth = XX m Volume per basin: approx. XXXX m3 Number of agitators: X unit per basin Max. Propeller diameter: 1,2 m The supplier must guarantee the following performance. Required performance and max. Power consumption. Propeller speed: XX min⁻¹ Guaranteed thrust per Agitator: > XXX N Max. Power consumption: XX kW (P1*) Specif. Thrust vs. power: XXX N / kW (F / P1) according to ISO 21630 Specif. Energy consumption: XX W / m3 (P1/ V) <i>P1* Total power consumption from grid</i>		
1.01		Submersible Agitator The agitator shall be suitable for mixing screened wastewater. The agitator shall be equipped with a roller guide with which it can be lowered and raised into the tank on a 100x100 mm guide rail without the need for personnel to enter the tank. During operation, the agitator shall be fixed by a stand with a vibration-absorbing rubber buffer. The agitator, the motor and the cable, shall be capable of continuous submergence without loss of watertight integrity to a depth of 20 m according to IP 68. Max. Motor speed: 1450 rpm Motor efficiency class.: IE3 Max. rated propeller speed: XX rpm Rated Power P2: >= XX kW Operating voltage: 400 V 50 Hz Starting method: Direct online Motor The motor shall be a submersible motor to IP 68 and the stator shall have class H insulation (180°C). The motor shall be capable of at least 30 evenly distributed starts per hour. The stator shall have one thermal switch per winding to monitor the motor temperature. On request the supplier shall provide a motor performance chart showing curves for torque, current, power factor, input power, output power, efficiency, and data on starting and no-load characteristics.	X,-	X,-

Fill in the Data for XXX and delete text of alternative which is not applicable

		The motor shall be equipped with 10m submersible and screened cable including 2 leads for the sensors. The cable entry seal shall consist of cylindrical elastomer bushings. Gear Unit The reduction of the motor speed to the propeller speed shall be carried out by a Two-step helical gearbox in an oil bath. The calculated service life of the gearbox shall be at least 100,000 h according to ISO 281. The gear box chamber shall be filled with a gear box oil of type Mobil gear 630 or similar. Oil housing and mechanical seals In addition to the gear box the Agitator shall have an oil chamber for the shaft sealing system with the option to equip it with a conductive seal monitoring. In addition to the gearbox, the agitator shall have an oil housing for the shaft seals and the possible connection of a conductive seal monitoring system. The outer seal of the propeller shaft shall be a mechanical seal made of corrosion-resistant cemented carbide (WCCR) and shall be suitable for direct contact with the medium. The inner seals shall be rubber lip seals. All seals shall be sufficiently lubricated and cooled by the oil. All seals must be maintenance-free. The oil chamber shall be filled with a medical white oil of paraffin type. The oil shall be free from aromatic hydrocarbons and be approved according to FDA 172.878. Propeller Unit The agitator shall be designed as a self-cleaning 3-bladed propeller with a backward curved leading edge. The pitch of the blades shall be positive and any adjustment or loosening of the blades during operation shall be excluded by design. The propeller diameter shall be 1200 mm. Material Motor and Gear box : Cast iron EN1561-GJL250 Propeller : Stainless steel 316L Support frame : Stainless steel 316L Shaft : AISI 420 / DIN 1.4057 Fasteners : AISI 316 / DIN 1.4436 Coating All wet parts made of cast iron shall be sandblasted in accordance with ISO 8501-1 Sa 2 ½. and ISO 8503-2. The surfaces shall be coated with 2 layers of Duasolid 50. The total layer thickness must be at least 350 ym. Factory testing On request the manufacturer shall be able to test the thrust and the power of the mixer according to ISO 21630:2007. The supplier shall present an assembly control plan according to ISO 9001, which confirms the execution of the following tests. 1. Tightness test of the assembled mixer using a vacuum method. 2. Dry-run test to establish mechanical integrity and correct rotation. The factory producing the mixing equipment shall be certified. according to ISO 9001 (quality): ISO 14001 (environmental) and OHSAS 18001 (occupational health and safety) standards. Model: FLYGT SR 4530 or equivalent		
--	--	---	--	--

1.011		CFD (Computational Fluid Dynamics) Analysis The Contractor shall submit the following information for review and approval: License and Software Proof of the employed CAD, CFD or any additional CFD Pre/Postprocessing software shall be shown on demand. This can include a copy of a paid license receipt or any other document supporting the claim. Finite volume based CFD software capable of multiphase modelling shall be used. CFD model Turbulence effects shall be represented with the help of realizable k-e (or other) model that provides an improved prediction for the spreading rate of both planar and round jets. Submersible mixer shall be modelled appropriately and correctly account for generated thrust, torque and radial forces. Apparent viscosity of the liquid shall lie between 1-10 cP based on the given TS concentration. Computational mesh shall adequately represent relevant internal obstacle and tank geometry with 0.1 m as a maximum size of the computational element. Wall effects shall be well resolved with the corresponding y+ value below 100. Gas-liquid two-way coupling shall be applied. Reported results shall correspond to a converged numerical solution. Proof of convergence in a form of residual plot and volume average velocity magnitude shall be presented. The volume average velocity shall be proven converged. The total air mass imbalance shall be maximum 5%. The total mass imbalance for net through flow cases shall be maximum 3%. CFD results The report shall describe problem at hand, agreed work scope and analysed scenarios. This shall include setup for each scenario, corresponding running conditions, flow rates, chosen mixer equipment and other relevant information. For the sake of clarity, geometry shall be shown in different perspective (side, top and isometric), important dimensions shall be specified, and all relevant internal objects and obstacles shall be shown. Boundary conditions and other modelling assumptions shall be presented and justified. Presented results shall build a solid understanding of the resulting flow pattern. Important flow features shall be visualized. Sedimentation risks shall be evaluated and, if necessary, addressed. Air entrainment risks near mixers shall be evaluated. Volumetric mean age distribution shall be provided for net through flow cases in order to evaluate short-circuiting/stagnation risks. To allow for independent audit of the numerical solution and to eliminate CFD model propriety risks, result files shall be, on demand, submitted in a format that is compatible with the Tecplot visual analysis tool.		
1.02		Installation set for permanent installation of Submersible agitator. The installation set shall contain: 1 freestanding tripod guide bar 100x100x 4mm for floor mounting including anchor bolts.	X,-	X,-

		The guide bar shall be applicable for an installation depth up to 6 m The guide bar shall have a support for the agitator. During operation, the wire shall not suspend the agitator. The guide bar and anchor bolts shall be made of AISI 316 (1.4571) The supplier of the agitator shall provide an installation drawing with detailed instruction about the position and orientation of the Agitator.		
1.02A		Installation set for permanent installation of Submersible agitator. The installation set shall contain: 1 freestanding tripod guide bar 100x100x 4mm for floor mounting including anchor bolts. The guide bar shall be applicable for an installation depth up to 6 m The guide bar shall have a support for the agitator. During operation, the wire shall not suspend the agitator. The guide bar and anchor bolts shall be made of AISI 304 The supplier of the agitator shall provide an installation drawing with detailed instruction about the position and orientation of the Agitator.	X,-	X,-
1.03.		Mobile Lifting davit for Agitator or pump Adjustable for reach and height, Reach 650 - 1200 mm, Including Winch with bracket and 15-meter wire. Max. lifting load: 320 kg Material: David: Stainless steel EN 1.4301 or AISI 304 Winch: Stainless steel or Aluminium Hook & Lifting wire: Stainless steel AISI 316 Model: FLYGT SK 320 or equivalent	X,-	X,-
1.03A		Mobile Lifting davit for Agitator or pump Adjustable for reach and height, Reach 1600 - 2000 mm, Including Winch with bracket and 15-meter wire. Max. lifting load: 300 kg Material: David: Stainless steel EN 1.4301 or AISI 304 Winch: Stainless steel or Aluminium Hook & Lifting wire: Stainless steel AISI 316 Model: FLYGT SK 300 or equivalent	X,-	X,-
1.04		Lifting device with automatic hook Shall enable the operator to catch, lift, lower and release the Agitator below water level. Material: Stainless steel 1.4436 Model: FLYGT AVR 834126 or equivalent	X,-	X,-
1.05		Floor mounted David holder including anchor bolts Material: Stainless steel AISI 316	X,-	X,-
1.05A		Option: Wall mounted David holder including anchor bolts. Material: Stainless steel AISI 316	X,-	X,-
3.01		Delivery of described agitator and accessories according incoterm DAP to <u>XXXXXXXXXXXXXXXXXX</u>		X,-
3.02		Installation of described Agitator and accessories Under the condition that that the Basins are accessible with a truck and that lifting gear is available. Place of Installation: XXXXXXXXXXXXXXXXXXXX		X,-